

K-VSTO POM
Plugs

HANSA-FLEX

Properties

Working pressure	0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)
Operating temperature	-20 °C to +70 °C in air; +1 °C to +70 °C in water
Material	Acetalpolymerisat (POM)
Sealant	NBR





Note

Further information on request

Description

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Item

Identification	Colour	L1 (mm)	Nozzle (mm)
K- 07 40 29 11	red	28,0	4
K- 07 40 29 12	red	28,0	5
K- 07 40 29 13	red	30,0	6
K- 07 40 29 14	red	31,0	8
K- 07 40 29 15	red	36,5	10
K- 07 40 29 16	red	38,5	12
K- 07 40 29 17	black	45,0	15
K- 07 40 29 18	black	41,5	18
K- 07 40 29 19	black	45,0	22
K- 07 40 29 20	black	56,0	28

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.