

# K-WV 5/3 ELEKTROPNEU ZENT BELF 4V

5/3-way pilot valve, mid-position pressurised


**HANSA FLEX**

## Properties

|                       |  |
|-----------------------|--|
| Operating pressure    | 1.5 - 8 bar  |
| Temp. range           | -20 °C to +70 °C   |
| Flow rate measurement | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p$ = 1 bar |
| Electrical connection | Connector Type B acc. to ISO 4400                              |
| min. working pressure | 1,5 bar  |
| Protection IP         | IP 65  |
| Valve body            | Aluminium alloy  |



39



Mid-position pressurised  
Zentrum belüftet

## Note

Further information on request

## Item

| Identification | Connection | Vent port | Flow rate (L/min) | circuit diagram number | Voltage      | Size |
|----------------|------------|-----------|-------------------|------------------------|--------------|------|
| K- 07 15 04 03 | M 5        | M 5       | 250               | 39                     | 24 V DC      | 100  |
| K- 07 15 04 04 | G 1/8      | G 1/8     | 400               | 39                     | 24 V DC      | 100  |
| K- 07 15 04 05 | G 1/8      | G 1/8     | 550               | 39                     | 24 V DC      | 200  |
| K- 07 15 04 06 | G 1/4      | G 1/8     | 550               | 39                     | 24 V DC      | 200  |
| K- 07 15 04 07 | G 1/4      | G 1/4     | 950               | 39                     | 24 V DC      | 300  |
| K- 07 15 04 08 | G 3/8      | G 1/4     | 950               | 39                     | 24 V DC      | 300  |
| K- 07 15 04 09 | G 1/2"     | G 1/2     | 1600              | 39                     | 24 V DC      | 400  |
| K- 07 15 04 10 | M 5        | M 5       | 250               | 39                     | 230 V, 50 Hz | 100  |
| K- 07 15 04 11 | G 1/8      | G 1/8     | 400               | 39                     | 230 V, 50 Hz | 100  |
| K- 07 15 04 12 | G 1/8      | G 1/8     | 550               | 39                     | 230 V, 50 Hz | 200  |
| K- 07 15 04 13 | G 1/4      | G 1/8     | 550               | 39                     | 230 V, 50 Hz | 200  |
| K- 07 15 04 14 | G 1/4      | G 1/4     | 950               | 39                     | 230 V, 50 Hz | 300  |
| K- 07 15 04 15 | G 3/8      | G 1/4     | 950               | 39                     | 230 V, 50 Hz | 300  |
| K- 07 15 04 16 | G 1/2"     | G 1/2     | 1600              | 39                     | 230 V, 50 Hz | 400  |