

K-WV 5/3 ELEKTROPNEU ZENT BELF 4V

5/3-way pilot valve, mid-position pressurised

HANSA FLEX

Properties

| | |
|-----------------------|--|
| Operating pressure | 1.5 - 8 bar |
| Temp. range | -20 °C to +70 °C |
| Flow rate measurement | At P1 = 8 bar, P2 = 6 bar and pressure drop Δp = 1 bar |
| Electrical connection | Connector Type B acc. to ISO 4400 |
| min. working pressure | 1,5 bar |
| Protection IP | IP 65 |
| Valve body | Aluminium alloy |



39



Mid-position pressurised
Zentrum belüftet

Note

Further information on request

Item

| Identification | Connection | Vent port | Flow rate (L/min) | circuit diagram number | Voltage | Size |
|----------------|------------|-----------|-------------------|------------------------|--------------|------|
| K- 07 15 04 03 | M 5 | M 5 | 250 | 39 | 24 V DC | 100 |
| K- 07 15 04 04 | G 1/8 | G 1/8 | 400 | 39 | 24 V DC | 100 |
| K- 07 15 04 05 | G 1/8 | G 1/8 | 550 | 39 | 24 V DC | 200 |
| K- 07 15 04 06 | G 1/4 | G 1/8 | 550 | 39 | 24 V DC | 200 |
| K- 07 15 04 07 | G 1/4 | G 1/4 | 950 | 39 | 24 V DC | 300 |
| K- 07 15 04 08 | G 3/8 | G 1/4 | 950 | 39 | 24 V DC | 300 |
| K- 07 15 04 09 | G 1/2" | G 1/2 | 1600 | 39 | 24 V DC | 400 |
| K- 07 15 04 10 | M 5 | M 5 | 250 | 39 | 230 V, 50 Hz | 100 |
| K- 07 15 04 11 | G 1/8 | G 1/8 | 400 | 39 | 230 V, 50 Hz | 100 |
| K- 07 15 04 12 | G 1/8 | G 1/8 | 550 | 39 | 230 V, 50 Hz | 200 |
| K- 07 15 04 13 | G 1/4 | G 1/8 | 550 | 39 | 230 V, 50 Hz | 200 |
| K- 07 15 04 14 | G 1/4 | G 1/4 | 950 | 39 | 230 V, 50 Hz | 300 |
| K- 07 15 04 15 | G 3/8 | G 1/4 | 950 | 39 | 230 V, 50 Hz | 300 |
| K- 07 15 04 16 | G 1/2" | G 1/2 | 1600 | 39 | 230 V, 50 Hz | 400 |