# K-GMM H

Glycerine-filled pressure gauges, connection on rear

## Properties

| | |
|---|---|
| **Type** | 213.40 |
| **Design** | Glycerine-filled Bourdon-tube pressure gauge |
| **Application** | For gaseous or liquid media which do not corrode copper alloy,do not have high viscosity and do not crystallise |
| **Accuracy class** | 1,6 (Ø 63 mm), 1,0 (Ø 100 mm) |
| **Media temperature** | max. +60 °C |
| **Ambient temperature** | -20 °C to +60 °C |
| **Crimp ring** | CrNi steel |
| **Housing** | Pressed brass |
| **Measuring element** | Copper alloy (Ø 63), Copper alloy < 100 bar\ nCrNi steel 1.4571 ≥ 100 bar (Ø 100) |
| **Inspection glass** | Plexiglass |
| **Movement** | Copper alloy |




## Note

Further information on request

## Description

For measuring points with high dynamic pressure loads and vibrations

## Item

| Identification | Measuring range | Ø (mm) | Connection |
|---|---|---|---|
| **K- 07 20 02 56** | -1 / 0.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 57** | 0 - 1.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 58** | 0 - 1.6 bar | 100,0 | G 1/2" |
| **K- 07 20 02 59** | 0 - 2.5 bar | 100,0 | G 1/2" |
| **K- 07 20 02 60** | 0 - 4.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 61** | 0 - 6.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 62** | 0 - 10.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 63** | 0 - 16.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 64** | 0 - 25.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 65** | 0 - 40.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 66** | 0 - 60.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 67** | 0 - 100.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 68** | 0 - 160.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 69** | 0 - 250.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 70** | 0 - 400.0 bar | 100,0 | G 1/2" |
| **K- 07 20 02 71** | 0 - 600.0 bar | 100,0 | G 1/2" |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*