
K-FI METALLBEHAEL SICHT H GFilters with metal bowl, sight glass and »HW« mounting bracket, semi-automatic drain valve



Properties			
Input pressure	Max. 10 bar		
Media temperature	max. 70 °C		
Ambient temperature	Max. 70 °C		
Working pressure	1.5 - 9 bar		
Pore size in filter element	5 μm		
Sealant	NBR		
Housing	Die-cast aluminium		
Drain valve	Semi- or fully-automatic		
Flow rate measurement	At P1 = 8 bar, P2 = 6 bar and pressure drop Δp = 1 bar		
More information	User manual on request		





Item							
Identification	Thread	Flow rate	Α	В	С	D	Size
		(L/min)	(mm)		(mm)	(mm)	
K- 07 25 06 45	G 3/4	7800	85,0	256,0 mm	37,0	219,0	3
K- 07 25 06 47	G 1	7800	85,0	256,0 mm	37,0	219,0	3

Accessories	
K-ERSATZBEHAELTER G UND G-MINI POLY	Spare tanks »G« Series and »G- mini« Series Polycarbonat
K-SCHUTZKORB G	Protective cage
K-FILTERELEMENT	Filter element
K-HALTERBAUSATZ	Holder
K-VERBINDUNGELEMENTE	Connecting sets
K-WANDHALTER	Wall bracket