
# K-ZWEIHAND S KONSOLE KOMPL

Complete pushbutton panel

## Properties

| | |
|---|---|
| **Media** | Filtered, unlubricated compressed air |
| **Operating pressure** | 2.5 - 8 bar |
| **Temp. range** | -10 °C to +60 °C |
| **Connection** | Push-in fitting for pipe 4 mm |
| **Operation** | Pneumatic |
| **Flow rate air 6bar** | 85 Nl/min |
| **max. time-offset input signal** | 0,4 s |



## Note

Further information on request

## Description

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter.Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

## Item

| Identification | Designation |
|---|---|
| **K- 07 15 26 08** | Complete pushbutton panel with safety valve |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*