

# K-T-STECK VB RED

Union tees, unequal

**HANSA FLEX**

## Properties

<b>Working pressure</b>	Max. 15 bar, coarse vacuum
<b>Application</b>	Air, vacuum
<b>Recommended hoses</b>	PU or PA (nylon)
<b>Media</b>	Compressed air and all gases or liquids that are compatible with the materials
<b>Temp. range</b>	-20 °C to +80 °C
<b>Material</b>	Plastic, Nickel plated brass
<b>Contact pressure ring</b>	Plastic
<b>Pneumatic Type</b>	



## Note

Further information on request

## Description

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Item

Identification	for external hose Ø	L1 (mm)
K- 07 40 03 62	2 x 4 mm / 1 x 6 mm	19,0
K- 07 40 03 63	2 x 6 mm / 1 x 4 mm	19,0
K- 07 40 03 64	2 x 6 mm / 1 x 8 mm	22,0
K- 07 40 41 42	2 x 8 mm / 1 x 4 mm	22,0
K- 07 40 03 65	2 x 8 mm / 1 x 6 mm	22,5
K- 07 40 03 66	2 x 8 mm / 1 x 10 mm	27,5
K- 07 40 41 43	2 x 10 mm / 1 x 6 mm	27,1
K- 07 40 03 67	2 x 10 mm / 1 x 8 mm	27,9
K- 07 40 03 68	2 x 10 mm / 1 x 12 mm	28,9
K- 07 40 41 44	2 x 12 mm / 1 x 8 mm	28,5
K- 07 40 03 69	2 x 12 mm / 1 x 10 mm	29,3
K- 07 40 41 45	2 x 16 mm / 1 x 12 mm	31,8