
K-WTEH 3-TLG PC SCHU VARIOBLOC

Service units, 3-piece with polycarbonate bowl and bowl guard



Properties	
Input pressure	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Media temperature	max. 50 °C
Ambient temperature	Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)
Pore size in filter element	40 μm
Sealant	NBR
Spring bonnet	POM
Housing	Die-cast zinc
Diaphragm	NBR
Dropper	PA
Drain valve	Manual
Flow rate measurement	At P1 = 10 bar, P2 = 6 bar and pressure drop Δp = 1 bar





Note

Further information on request

Description

Two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

Ordering information

Service units are also available with bowl guard or metal bowl. Service units are also available in other control ranges (0.5 - 6 bar and 0.5 - 16 bar) and in lockable version. Please ask for more information.

Additional information

Service units are also available with bowl guard or metal bowl. Service units are also available in other control ranges.

Item Identification Thread Control range Flow rate В K- 07 25 22 86 G 1/4 0.5 - 10 bar 1500 144,0 201,0 mm 68,0 K- 07 25 22 85 G 3/8 0.5 - 10 bar 1800 144,0 201,0 mm 68,0 K- 07 25 22 84 G 1/2 0.5 - 10 bar 3400 210,0 247,0 mm 98,0 K- 07 25 22 83 G 3/4 0.5 - 10 bar 5000 210,0 247,0 mm 98,0 K- 07 25 22 82 G 1 0.5 - 10 bar 5000 264,0 247,0 mm 98,0