

# K-L-STECKVER DREH IG AG-K

Male elbows, swivel type, conical male and female threads, coated

**HANSA FLEX**

## Properties

<b>Working pressure</b>	Max. 15 bar, coarse vacuum
<b>Application</b>	Air, vacuum
<b>Recommended hoses</b>	PU or PA (nylon)
<b>Media</b>	Compressed air and all gases or liquids that are compatible with the materials
<b>Temp. range</b>	-20 °C to +80 °C
<b>Sealing surface</b>	Conical version: thread coating
<b>Material</b>	Plastic, Nickel plated brass
<b>Contact pressure ring</b>	Plastic



## Note

Further information on request

## Description

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Item

Identification	Thread	for external hose Ø	L1 (mm)	L2 (mm)	AF
K- 07 40 09 69	R/Rc 1/8	4 mm	22,3	29,5	14 mm
K- 07 40 09 70	R/Rc 1/8	6 mm	23,1	29,5	14 mm
K- 07 40 09 71	R/Rc 1/8	8 mm	25,6	29,5	14 mm
K- 07 40 09 68	R/Rc 1/8	10 mm	30,1	29,5	14 mm
K- 07 40 09 65	R/Rc 1/4	4 mm	24,1	34,3	17 mm
K- 07 40 09 66	R/Rc 1/4	6 mm	25,1	34,3	17 mm
K- 07 40 09 67	R/Rc 1/4	8 mm	28,6	34,3	17 mm
K- 07 40 09 63	R/Rc 1/4	10 mm	32,3	34,3	17 mm
K- 07 40 09 64	R/Rc 1/4	12 mm	33,5	34,3	17 mm
K- 07 40 09 74	R/Rc 3/8	6 mm	26,8	40,4	21 mm
K- 07 40 09 75	R/Rc 3/8	8 mm	29,6	40,4	21 mm
K- 07 40 09 72	R/Rc 3/8	10 mm	32,9	40,4	21 mm
K- 07 40 09 73	R/Rc 3/8	12 mm	35,6	40,4	21 mm
K- 07 40 09 61	R/Rc 1/2	6 mm	29,8	47,5	24 mm
K- 07 40 09 62	R/Rc 1/2	8 mm	32,6	47,5	24 mm
K- 07 40 09 59	R/Rc 1/2	10 mm	35,9	47,5	24 mm
K- 07 40 09 60	R/Rc 1/2	12 mm	36,6	47,5	24 mm