K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type

Properties

Operating pressure	Max. 10 bar
Flow rate air	1.800 l/min (at 6 bar and Δp = 1 bar)
Media temperature	-20 °C to +150 °C
Housing	Stainless steel 1.4404
Thread	Stainless steel 1.4404
Internal parts	Stainless steel 1.4404
Button, valve	Stainless steel 1.4404
Sealant	FKM



Note

Not suitable for hitting / pulsating tools.
Further information on request

Description

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Additional information

Not suitable for hitting / pulsating tools.

Item

Identification	Connection	Length (mm)	AF (mm)
K- 07 35 12 79	G 1/4 female	71,5	21
K- 07 35 12 80	G 3/8 female	75,5	21
K- 07 35 12 81	G 1/2 female	77,5	24

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.