K-LKM S NW7,4 DREH AG VA

Safety couplings DN 7.4, stainless steel 1.4404, male, swivel type



Properties			
Operating pressure	Max. 10 bar		
Flow rate air	1.800 l/min (at 6 bar and Δp = 1 bar)		
Media temperature	-20 °C to +150 °C		
Housing	Stainless steel 1.4404		
Thread	Stainless steel 1.4404		
Internal parts	Stainless steel 1.4404		
Button, valve	Stainless steel 1.4404		
Sealant	FKM		



Note

Not suitable for hitting / pulsating tools.

Further information on request

Description

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Additional information

Not suitable for hitting / pulsating tools.

Item				
Identification	Connection	Length	AF	
		(mm)	(mm)	
K- 07 35 12 76	G 1/4 male	70,5	21	
K- 07 35 12 77	G 3/8 male	70,0	21	
K- 07 35 12 78	G 1/2 male	72,5	25	