

# K-L-STECKVER IG DREH

Banjo elbows with parallel female thread, swivel type

**HANSA FLEX**

## Properties

<b>Working pressure</b>	Max. 15 bar, coarse vacuum
<b>Application</b>	Air, vacuum
<b>Recommended hoses</b>	PU or PA (nylon)
<b>Media</b>	Compressed air and all gases or liquids that are compatible with the materials
<b>Temp. range</b>	-20 °C to +80 °C
<b>Sealing surface</b>	Parallel version: O-ring in housing
<b>Material</b>	Plastic, Nickel plated brass
<b>Contact pressure ring</b>	Plastic



## Note

Further information on request

## Description

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Item

Identification	Thread	for external hose Ø	L1 (mm)	L2 (mm)	AF
K- 07 40 05 66	M 5	4 mm	17,5	18,5	10 mm
K- 07 40 05 67	M 5	6 mm	18,7	19,7	12 mm
K- 07 40 05 79	G 1/8	4 mm	17,7	23,0	14 mm
K- 07 40 05 80	G 1/8	6 mm	18,7	24,4	14 mm
K- 07 40 05 81	G 1/8	8 mm	22,5	27,3	14 mm
K- 07 40 05 78	G 1/8	10 mm	27,2	27,3	17 mm
K- 07 40 05 75	G 1/4	4 mm	17,5	26,0	17 mm
K- 07 40 05 76	G 1/4	6 mm	18,7	27,4	17 mm
K- 07 40 05 77	G 1/4	8 mm	22,5	30,3	17 mm
K- 07 40 05 73	G 1/4	10 mm	27,2	34,3	17 mm
K- 07 40 05 74	G 1/4	12 mm	29,3	37,0	21 mm
K- 07 40 05 85	G 3/8	6 mm	18,7	28,7	21 mm
K- 07 40 05 86	G 3/8	8 mm	22,5	32,0	21 mm
K- 07 40 05 82	G 3/8	10 mm	27,2	36,3	21 mm
K- 07 40 05 83	G 3/8	12 mm	29,3	38,0	21 mm
K- 07 40 05 84	G 3/8	16 mm	32,5	40,5	24 mm
K- 07 40 05 71	G 1/2	6 mm	18,7	34,2	24 mm
K- 07 40 05 72	G 1/2	8 mm	22,5	34,3	24 mm
K- 07 40 05 68	G 1/2	10 mm	27,2	38,8	24 mm
K- 07 40 05 69	G 1/2	12 mm	29,3	40,5	24 mm
K- 07 40 05 70	G 1/2	16 mm	32,5	43,0	24 mm