


# K-W90BK MINI

angle mini ball valves

**HANSA FLEX**

## Properties

|                              |                                |
|------------------------------|--------------------------------|
| <b>Application</b>           | Compressed air, water, oil     |
| <b>Operating pressure</b>    | -0,99 bar - 20 bar             |
| <b>Operating temperature</b> | -20 °C to +80 °C               |
| <b>Thread description</b>    | G thread acc. DIN EN ISO 228-1 |
| <b>Housing and ball</b>      | Chrome-plated brass            |
| <b>Hand lever</b>            | PA 66 glass fibre-reinforced   |
| <b>Ball seals</b>            | PTFE                           |
| <b>Stem seal</b>             | NBR                            |



## Note

Further information on request

## Item

| Identification | DN | Thread       | G<br>(mm) | H1<br>(mm) | H2<br>(mm) | L<br>(mm) | AF1<br>(mm) | AF2<br>(mm) |
|----------------|----|--------------|-----------|------------|------------|-----------|-------------|-------------|
| K- 07 30 29 84 | 5  | G 1/8 female | 19,00     | 33,5       | 15,5       | 28,5      | 17          | 17          |
| K- 07 30 29 85 | 5  | G 1/4 female | 19,00     | 33,5       | 17,5       | 28,5      | 17          | 17          |
| K- 07 30 29 86 | 7  | G 3/8 female | 19,00     | 35,0       | 19,5       | 31,0      | 17          | 21          |