

# K-L-STECKVER AG-K VA

Male elbows conical male thread

**HANSA FLEX**

## Properties

<b>Working pressure pulsate</b>	Max. 10 bar
<b>Pressure</b>	Max. 15 bar (depending on pipe quality)
<b>Suitable pipe materials</b>	PVDF, PTFE, stainless steel, PA, PU
<b>Standard</b>	R thread acc. to ISO 7-1
<b>Ambient temperature</b>	-20 °C to max. +150 °C (depending on pipe quality and diameter)
<b>Material</b>	Stainless steel 1.4404
<b>Sealant</b>	FKM



## Note

Further information on request

## Description

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Item

Identification	Thread	for external hose Ø	L1 (mm)	L2 (mm)
K- 07 40 24 37	R 1/8	4 mm	17,0	16,0
K- 07 40 24 38	R 1/8	6 mm	20,0	16,0
K- 07 40 24 39	R 1/8	8 mm	21,0	17,0
K- 07 40 24 35	R 1/4	6 mm	20,0	20,0
K- 07 40 24 36	R 1/4	8 mm	21,0	20,0
K- 07 40 46 80	R 1/4	10 mm	25,5	22,5