# K-SOFT PVC SET SVKM TUE NW7,2

Soft PVC workshop hose kits with quick diconnect couplings and stems DN 7.2

## Properties

| | |
|---|---|
| **Inner layer** | Soft-PVC, black |
| **Insert** | polyester braid |
| **Outer layer** | Soft-PVC, blue |
| **Operating temperature** | -20 °C to +60 °C |



## Note

Further information on request

## Description

Highly flexible hose for compressed air applications in workshop areas. Assembled wit brass stem and brass quick disconnect coupling DN 7.2

## Item

| Identification | Ø hose internal (mm) | Ø hose external (mm) | max. working pressure at 20° C (bar) | Hose lenght (m) |
|---|---|---|---|---|
| **K- 07 10 11 91** | 6,3 | 11,0 | 15 | 5 |
| **K- 07 10 11 85** | 6,3 | 11,0 | 15 | 10 |
| **K- 07 10 11 87** | 6,3 | 11,0 | 15 | 15 |
| **K- 07 10 11 88** | 6,3 | 11,0 | 15 | 20 |
| **K- 07 10 11 90** | 6,3 | 11,0 | 15 | 25 |
| **K- 07 10 11 99** | 9,0 | 14,5 | 15 | 5 |
| **K- 07 10 11 93** | 9,0 | 14,5 | 15 | 10 |
| **K- 07 10 11 95** | 9,0 | 14,5 | 15 | 15 |
| **K- 07 10 11 96** | 9,0 | 14,5 | 15 | 20 |
| **K- 07 10 11 98** | 9,0 | 14,5 | 15 | 25 |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*