K-SOFT PVC SET SVKM TUE NW7,2

Soft PVC workshop hose kits with quick diconnect couplings and stems DN 7.2

HANSA-FLEX

Properties

Inner layer	Soft-PVC, black
Insert	polyester braid
Outer layer	Soft-PVC, blue
Operating temperature	-20 °C to +60 °C



Note

Further information on request

Description

Highly flexible hose for compressed air applications in workshop areas. Assembled wit brass stem and brass quick disconnect coupling DN 7.2

Item

Identification	Ø hose internal (mm)	Ø hose external (mm)	max. working pressure at 20° C (bar)	Hose lenght (m)
K- 07 10 11 91	6,3	11,0	15	5
K- 07 10 11 85	6,3	11,0	15	10
K- 07 10 11 87	6,3	11,0	15	15
K- 07 10 11 88	6,3	11,0	15	20
K- 07 10 11 90	6,3	11,0	15	25
K- 07 10 11 99	9,0	14,5	15	5
K- 07 10 11 93	9,0	14,5	15	10
K- 07 10 11 95	9,0	14,5	15	15
K- 07 10 11 96	9,0	14,5	15	20
K- 07 10 11 98	9,0	14,5	15	25

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.