


# K-T-STECK VB 3

Union tees

**HANSA FLEX**

## Properties

|                       |                     |
|-----------------------|---------------------|
| Working pressure      | Max. 16 bar         |
| Operating temperature | -20 °C to +80 °C    |
| Material              | Nickel-plated brass |
| Contact pressure ring | Hostaform           |
| Clamping ring         | Stainless steel     |



## Note

Further information on request

## Description

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Item

| Identification | for external hose Ø | L1<br>(mm) | L2<br>(mm) |
|----------------|---------------------|------------|------------|
| K- 07 40 25 42 | 3 mm                | 21,2       | 10,4       |
| K- 07 40 25 43 | 4 mm                | 33,4       | 16,7       |
| K- 07 40 25 44 | 5 mm                | 38,4       | 19,2       |
| K- 07 40 25 45 | 6 mm                | 38,0       | 19,0       |
| K- 07 40 25 46 | 8 mm                | 42,6       | 21,3       |
| K- 07 40 25 47 | 10 mm               | 46,6       | 23,3       |
| K- 07 40 25 48 | 12 mm               | 52,0       | 26,0       |
| K- 07 40 25 49 | 14 mm               | 58,6       | 29,3       |