


# K-BOX CLICK-CLOCK

Boxed set - click-clock

**HANSA** **FLEX**

## Properties

|                       |                     |
|-----------------------|---------------------|
| Working pressure      | Max. 16 bar         |
| Operating temperature | -20 °C to +80 °C    |
| Material              | Nickel-plated brass |
| Contact pressure ring | Hostaform           |
| O-ring                | NBR                 |
| Clamping ring         | Stainless steel     |



## Description

45 male connectors G 1/8-4, G 1/8-6, G 1/4-8, G 3/8-8  
35 swivel type male elbows G 1/8-4, G 1/8-6, G 1/4-6, G 1/4-8, G 3/8-8  
15 unions 4, 6, 8 mm  
10 union elbows 6, 8 mm  
15 union tees 4, 6, 8 mm  
15 swivel type male branch tees G 1/8-6, G 1/4-6, G 1/4-8  
9 reducers with push-in plug 8/6, 10/6, 10/8  
10 plugs 6, 8 mm  
10 sockets G 1/8, G 1/4, G 3/8  
1 PTFE-sealing tape  
1 hose cutter

## Additional information

Further types and dimensions on request.

## Item

| Identification | Designation                                      |
|----------------|--|
| K- 07 40 35 24 | Boxed set, >click-clock< Series push-in fittings |