


# K-STECKVERSCHR AGR OR SK

Male connectors, parallel male thread with O-ring and outer hex

**HANSA****FLEX**

## Properties

Working pressure	Max. 15 bar, coarse vacuum
Application	Air, vacuum
Recommended hoses	PU or PA (nylon)
Media	Compressed air and all gases or liquids that are compatible with the materials
Temp. range	-20 °C to +80 °C
Sealing surface	Parallel version: O-ring in housing
Material	Plastic, Nickel plated brass
Contact pressure ring	Plastic



## Note

Further information on request

## Description

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Item

Identification	Thread	for external hose Ø	hexagon socket (mm)	L1 (mm)	AF
K-07 40 00 78	M 5	4 mm	2,0	20,8	10 mm
K-07 40 00 79	M 5	6 mm	2,0	22,2	12 mm
K-07 40 00 92	G 1/8	4 mm	3,0	19,3	10 mm
K-07 40 00 93	G 1/8	6 mm	4,0	20,2	12 mm
K-07 40 00 94	G 1/8	8 mm	5,0	27,1	14 mm
K-07 40 00 90	G 1/8	10 mm	5,0	28,9	17 mm
K-07 40 00 91	G 1/8	12 mm	5,0	31,6	21 mm
K-07 40 00 87	G 1/4	4 mm	3,0	17,4	10 mm
K-07 40 00 88	G 1/4	6 mm	4,0	20,9	12 mm
K-07 40 00 89	G 1/4	8 mm	6,0	23,0	14 mm
K-07 40 00 85	G 1/4	10 mm	6,0	29,9	17 mm
K-07 40 00 86	G 1/4	12 mm	6,0	32,6	21 mm
K-07 40 00 98	G 3/8	6 mm	4,0	19,5	12 mm
K-07 40 00 99	G 3/8	8 mm	6,0	22,1	14 mm
K-07 40 00 95	G 3/8	10 mm	8,0	25,9	17 mm
K-07 40 00 96	G 3/8	12 mm	8,0	28,6	21 mm
K-07 40 00 97	G 3/8	16 mm	8,0	36,1	24 mm
K-07 40 00 83	G 1/2	6 mm	4,0	22,6	12 mm
K-07 40 00 84	G 1/2	8 mm	6,0	23,2	14 mm
K-07 40 00 80	G 1/2	10 mm	8,0	24,5	17 mm
K-07 40 00 81	G 1/2	12 mm	8,0	31,1	21 mm
K-07 40 00 82	G 1/2	16 mm	10,0	38,1	24 mm