


# K-Y-WINKELVERSCH DRE AG OR

Male branch Y-elbows with outer hex, swivel type, parallel male thread with O-ring

**HANSA FLEX**

## Properties

<b>Working pressure</b>	Max. 15 bar, coarse vacuum
<b>Application</b>	Air, vacuum
<b>Recommended hoses</b>	PU or PA (nylon)
<b>Media</b>	Compressed air and all gases or liquids that are compatible with the materials
<b>Temp. range</b>	-20 °C to +80 °C
<b>Sealing surface</b>	Parallel version: O-ring in housing
<b>Material</b>	Plastic, Nickel plated brass
<b>Contact pressure ring</b>	Plastic



## Note

Further information on request

## Description

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Item

Identification	Thread	for external hose Ø	L1 (mm)	L2 (mm)	AF
K- 07 40 43 07	M 5	4 mm	24,0	22,0	12 mm
K- 07 40 43 10	G 1/8	6 mm	24,0	25,0	12 mm
K- 07 40 43 09	G 1/4	8 mm	28,5	28,8	14 mm
K- 07 40 43 11	G 3/8	10 mm	33,7	34,8	19 mm
K- 07 40 43 08	G 1/2	12 mm	37,5	42,1	24 mm