

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Properties

Inner layer	Soft-PVC, black
Insert	polyester braid
Outer layer	Soft-PVC, blue
Temperature	-20 °C to +60 °C
Roll length	50 m



Note

Further information on request

Description

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Item				
Identification	Ø hose internal (mm)	Ø hose external (mm)	Max. working pressure resistance at 23°C (bar)	Min. bending radius (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88