


K-STECKVERBINDU RED 1

Reducers

HANSA FLEX

Properties

| | |
|-----------------------|---------------------|
| Working pressure | Max. 16 bar |
| Operating temperature | -20 °C to +80 °C |
| Material | Nickel-plated brass |
| Contact pressure ring | Hostaform |
| Clamping ring | Stainless steel |



Note

Further information on request

Description

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Item

| Identification | Thread | for external hose Ø | L1 (mm) |
|----------------|----------|---------------------|------------|
| K- 07 40 25 26 | M 13 x 1 | 4 mm / 6 mm | 32,7 |
| K- 07 40 25 27 | M 15 x 1 | 4 mm / 8 mm | 34,4 |
| K- 07 40 25 28 | M 15 x 1 | 6 mm / 8 mm | 35,0 |
| K- 07 40 25 29 | M 17 x 1 | 6 mm / 10 mm | 37,5 |
| K- 07 40 25 30 | M 20 x 1 | 6 mm / 12 mm | 39,0 |
| K- 07 40 25 31 | M 17 x 1 | 8 mm / 10 mm | 37,8 |
| K- 07 40 25 32 | M 20 x 1 | 8 mm / 12 mm | 40,1 |
| K- 07 40 25 33 | M 20 x 1 | 10 mm / 12 mm | 40,8 |