

# K-DLV MULTI-LINK STANDARD

Compressed air distributor, type »Multi-Link« with quick disconnect standard couplings DN 7.6

**HANSA FLEX**

## Properties

|                           |                                     |
|---------------------------|-------------------------------------|
| <b>Operating pressure</b> | Max. 16 bar                         |
| <b>Temp. range</b>        | -20 °C to +100 °C                   |
| <b>Material</b>           | Galvanised steel / brass            |
| <b>Connection</b>         | G 1/2 female                        |
| <b>Media</b>              | Compressed air, non-corrosive gases |
| <b>Sealant</b>            | NBR                                 |



## Note

Further information on request

## Description

Modular distributor system for flexible workplace design, can be rotated 180°. Equipped for 1 to 5 bleed units:  
- DN 7.6 standard quick disconnect couplings.

## Item

| Identification | Connection                | Bleed units |
|----------------|---------------------------|-------------|
| K- 07 35 13 69 | Standard couplings DN 7.6 | 1           |
| K- 07 35 13 72 | Standard couplings DN 7.6 | 2           |
| K- 07 35 13 75 | Standard couplings DN 7.6 | 3           |
| K- 07 35 13 78 | Standard couplings DN 7.6 | 4           |
| K- 07 35 13 81 | Standard couplings DN 7.6 | 5           |