K-DURCHGANGSVERTEILERDOSE

Through porting box with through-hole thread, PN 15

Properties

Operating pressure	Max. 15 bar
torque mounting hole	4 Nm
torque brass thread	12 Nm
Temp. range	-10 °C to +50 °C
Housing	Glass fibre-reinforced plastic
Thread	Brass



Note

Further information on request

Description

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

Item

Identification	Thread inlet	Through-hole thread	Connecting thread
K- 07 40 48 04	G 1/2"	G 1/2	1 x G 1/2
K- 07 40 48 05	G 1/2"	G 1/2	2 x G 1/2
K- 07 40 48 06	G 1/2"	G 1/2	3 x G 1/2
K- 07 40 48 07	G 3/4"	G 3/4	1 x G 1/2
K- 07 40 48 08	G 3/4"	G 3/4	2 x G 1/2
K- 07 40 48 09	G 3/4"	G 3/4	3 x G 1/2

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.