

# K-T-STECK VERS DRE AG-K VA

Male branch tees, swivel type, conical male thread

**HANSA FLEX**

## Properties

|                          |   |
|--------------------------|---|
| Working pressure pulsate | Max. 10 bar   |
| Pressure                 | Max. 15 bar (depending on pipe quality)                         |
| Suitable pipe materials  | PVDF, PTFE, stainless steel, PA, PU                             |
| Standard                 | R thread acc. to ISO 7-1  |
| Ambient temperature      | -20 °C to max. +150 °C (depending on pipe quality and diameter) |
| Material                 | Stainless steel 1.4404  |
| Sealant                  | FKM   |



## Note

Further information on request

## Description

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Item

| Identification | Thread | for external hose Ø | L1<br>(mm) | L2<br>(mm) | AF    |
|----------------|--------|---------------------|------------|------------|-------|
| K- 07 40 24 59 | R 1/8  | 4 mm                | 34,0       | 21,5       | 10 mm |
| K- 07 40 24 60 | R 1/8  | 6 mm                | 42,0       | 24,5       | 13 mm |
| K- 07 40 24 61 | R 1/8  | 8 mm                | 43,0       | 24,5       | 13 mm |
| K- 07 40 24 57 | R 1/4  | 6 mm                | 42,0       | 28,5       | 14 mm |
| K- 07 40 24 58 | R 1/4  | 8 mm                | 43,0       | 28,5       | 14 mm |
| K- 07 40 24 56 | R 1/4  | 10 mm               | 50,0       | 32,0       | 16 mm |
| K- 07 40 24 62 | R 3/8  | 10 mm               | 50,0       | 32,5       | 17 mm |