

K-ROHRDOPPELNIPPEL VA

Double pipe nipples, stainless steel 1.4571

HANSA FLEX

Properties

Working pressure	Max. 20 bar
Connecting thread	R-thread to EN 10226
Material	Stainless steel 1.4571



Note

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Further information on request

Item

Identification	Thread	Length (mm)
K- 07 40 48 61	R 1/4	40,0
K- 07 40 48 62	R 1/4	60,0
K- 07 40 48 63	R 1/4	80,0
K- 07 40 48 56	R 1/4	100,0
K- 07 40 48 57	R 1/4	120,0
K- 07 40 48 58	R 1/4	150,0
K- 07 40 48 59	R 1/4	180,0
K- 07 40 48 60	R 1/4	200,0
K- 07 40 48 85	R 3/8	40,0
K- 07 40 48 86	R 3/8	60,0
K- 07 40 48 87	R 3/8	80,0
K- 07 40 48 80	R 3/8	100,0
K- 07 40 48 81	R 3/8	120,0
K- 07 40 48 82	R 3/8	150,0
K- 07 40 48 83	R 3/8	180,0
K- 07 40 48 84	R 3/8	200,0
K- 07 40 48 53	R 1/2	40,0
K- 07 40 48 54	R 1/2	60,0
K- 07 40 48 55	R 1/2	80,0
K- 07 40 48 48	R 1/2	100,0
K- 07 40 48 49	R 1/2	120,0
K- 07 40 48 50	R 1/2	150,0
K- 07 40 48 51	R 1/2	180,0
K- 07 40 48 52	R 1/2	200,0
K- 07 40 48 77	R 3/4	40,0
K- 07 40 48 78	R 3/4	60,0
K- 07 40 48 79	R 3/4	80,0
K- 07 40 48 72	R 3/4	100,0
K- 07 40 48 73	R 3/4	120,0
K- 07 40 48 74	R 3/4	150,0
K- 07 40 48 75	R 3/4	180,0
K- 07 40 48 76	R 3/4	200,0
K- 07 40 48 29	R 1	40,0
K- 07 40 48 30	R 1	60,0
K- 07 40 48 31	R 1	80,0
K- 07 40 40 93	R 1	150,0
K- 07 40 48 25	R 1	100,0
K- 07 40 48 26	R 1	120,0
K- 07 40 48 27	R 1	180,0
K- 07 40 48 28	R 1	200,0
K- 07 40 48 45	R 1 1/4	40,0
K- 07 40 48 46	R 1 1/4	60,0
K- 07 40 48 47	R 1 1/4	80,0
K- 07 40 48 40	R 1 1/4	100,0
K- 07 40 48 41	R 1 1/4	120,0



Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.

24.05.2026

HANSA-FLEX AG

www.hansa-flex.com

1

K-ROHRDOPPELNIPPEL VA

Double pipe nipples, stainless steel 1.4571

Item		
Identification	Thread	Length (mm)
K- 07 40 48 42	R 1 1/4	150,0
K- 07 40 48 43	R 1 1/4	180,0
K- 07 40 48 44	R 1 1/4	200,0
K- 07 40 48 37	R 1 1/2	40,0
K- 07 40 48 38	R 1 1/2	60,0
K- 07 40 48 39	R 1 1/2	80,0
K- 07 40 48 32	R 1 1/2	100,0
K- 07 40 48 33	R 1 1/2	120,0
K- 07 40 48 34	R 1 1/2	150,0
K- 07 40 48 35	R 1 1/2	180,0
K- 07 40 48 36	R 1 1/2	200,0
K- 07 40 48 69	R 2	40,0
K- 07 40 48 70	R 2	60,0
K- 07 40 48 71	R 2	80,0
K- 07 40 48 64	R 2	100,0
K- 07 40 48 65	R 2	120,0
K- 07 40 48 66	R 2	150,0
K- 07 40 48 67	R 2	180,0
K- 07 40 48 68	R 2	200,0