

K-SCHMUTZFAENGER MS BL

Strainers - brass

HANSA FLEX

Properties

| | |
|-----------------------|--|
| Operating pressure | Max. 20 bar |
| Operating temperature | -20 °C to +110 °C |
| Thread description | G-thread acc. ISO 228-1, tolerance class B |
| Screen | Stainless steel, mesh size 0.5 mm |
| Housing | Brass with a bare metal surface |
| Head piece | Brass with a bare metal surface |
| Seals | NBR O-ring |



Note

Further information on request

Description

Suitable for domestic water services, heating and air conditioning plants or compressed air systems. Not suitable for steam.

Item

| Identification | DN | Thread | C (mm) | L (mm) | AF1 (mm) | AF2 (mm) |
|----------------|----|---------|-----------|-----------|-------------|-------------|
| K- 07 30 29 93 | 8 | G 1/4 | 40,0 | 55,0 | 18 | 20 |
| K- 07 30 29 94 | 10 | G 3/8 | 40,0 | 55,0 | 21 | 20 |
| K- 07 30 29 95 | 15 | G 1/2 | 40,0 | 58,0 | 25 | 20 |
| K- 07 30 29 96 | 20 | G 3/4 | 48,0 | 70,0 | 31 | 27 |
| K- 07 30 29 97 | 25 | G 1 | 56,0 | 87,0 | 38 | 32 |
| K- 07 30 29 98 | 32 | G 1 1/4 | 64,0 | 96,0 | 47 | 36 |
| K- 07 30 29 99 | 40 | G 1 1/2 | 73,0 | 106,0 | 57 | 38 |
| K- 07 30 30 00 | 50 | G 2 | 89,0 | 126,0 | 67 | 46 |