
K-SCHMUTZFAENGER MS BL

Strainers - brass



Properties	
Operating pressure	Max. 20 bar
Operating temperature	-20 °C to +110 °C
Thread description	G-thread acc. ISO 228-1, tolerance class B
Screen	Stainless steel, mesh size 0.5 mm
Housing	Brass with a bare metal surface
Head piece	Brass with a bare metal surface
Seals	NBR O-ring





Note

Further information on request

Description

Suitable for domestic water services, heating and air conditioning plants or compressed air systems. Not suitable for steam.

Item							
DN	Thread	C (mm)	L (mm)	AF1 (mm)	AF2 (mm)		
8	G 1/4	40,0	55,0	18	20		
10	G 3/8	40,0	55,0	21	20		
15	G 1/2	40,0	58,0	25	20		
20	G 3/4	48,0	70,0	31	27		
25	G 1	56,0	87,0	38	32		
32	G 1 1/4	64,0	96,0	47	36		
40	G 1 1/2	73,0	106,0	57	38		
50	G 2	89,0	126,0	67	46		
	8 10 15 20 25 32 40	8 G 1/4 10 G 3/8 15 G 1/2 20 G 3/4 25 G 1 32 G 1 1/4 40 G 1 1/2	8 G 1/4 40,0 10 G 3/8 40,0 15 G 1/2 40,0 20 G 3/4 48,0 25 G 1 56,0 32 G 1 1/4 64,0 40 G 1 1/2 73,0	(mm) (mm) 8 G 1/4 40,0 55,0 10 G 3/8 40,0 55,0 15 G 1/2 40,0 58,0 20 G 3/4 48,0 70,0 25 G 1 56,0 87,0 32 G 1 1/4 64,0 96,0 40 G 1 1/2 73,0 106,0	(mm) (mm) (mm) 8 G 1/4 40,0 55,0 18 10 G 3/8 40,0 55,0 21 15 G 1/2 40,0 58,0 25 20 G 3/4 48,0 70,0 31 25 G 1 56,0 87,0 38 32 G 1 1/4 64,0 96,0 47 40 G 1 1/2 73,0 106,0 57		