

# K-SCHMUTZFAENGER MS BL

Strainers - brass

**HANSA FLEX**

## Properties

<b>Operating pressure</b>	Max. 20 bar
<b>Operating temperature</b>	-20 °C to +110 °C
<b>Thread description</b>	G-thread acc. ISO 228-1, tolerance class B
<b>Screen</b>	Stainless steel, mesh size 0.5 mm
<b>Housing</b>	Brass with a bare metal surface
<b>Head piece</b>	Brass with a bare metal surface
<b>Seals</b>	NBR O-ring



## Note

Further information on request

## Description

Suitable for domestic water services, heating and air conditioning plants or compressed air systems. Not suitable for steam.

## Item

Identification	DN	Thread	C (mm)	L (mm)	AF1 (mm)	AF2 (mm)
K- 07 30 29 93	8	G 1/4	40,0	55,0	18	20
K- 07 30 29 94	10	G 3/8	40,0	55,0	21	20
K- 07 30 29 95	15	G 1/2	40,0	58,0	25	20
K- 07 30 29 96	20	G 3/4	48,0	70,0	31	27
K- 07 30 29 97	25	G 1	56,0	87,0	38	32
K- 07 30 29 98	32	G 1 1/4	64,0	96,0	47	36
K- 07 30 29 99	40	G 1 1/2	73,0	106,0	57	38
K- 07 30 30 00	50	G 2	89,0	126,0	67	46