

# K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

**HANSA FLEX**

## Properties

<b>Application</b>	Air, gases, oils, greases, fuels, organic and inorganic substances
<b>Operating temperature</b>	-40 °C to +100 °C
<b>Pneumatic Type</b>	connection nipples and coupling NW 7,2



## Note

Further information on request

## Description

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Item

Identification	Ø hose internal (mm)	Ø hose external (mm)	Ø spiral external (mm)	coils	Max. working pressure resistance at 23°C (bar)	max. working length (m)
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

## Accessories

<b>K-DREHBARE VERSCHR KNICK</b>	Swivel adapters with kink protector
<b>K-STARRE VERSCHRAUBUNG</b>	Rigid adapters with kink protector