K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling



Properties		
Application	Air, gases, oils, greases, fuels, organic and inorganic substances	
Operating temperature	-40 °C to +100 °C	
Pneumatic Type	connection nipples and coupling NW 7,2	



Note

Further information on request

Description

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Item						
Identification	Ø hose internal	Ø hose external	Ø spiral external (mm)	coils	Max. working pressure resistance at 23°C (bar)	max. working length
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

Accessories	
K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector