

K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

HANSA FLEX

Properties

| | |
|------------------------------|--|
| Application | Air, gases, oils, greases, fuels, organic and inorganic substances |
| Operating temperature | -40 °C to +100 °C |
| Pneumatic Type | connection nipples and coupling NW 7,2 |



Note

Further information on request

Description

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Item

| Identification | Ø hose internal (mm) | Ø hose external (mm) | Ø spiral external (mm) | coils | Max. working pressure resistance at 23°C (bar) | max. working length (m) |
|----------------|----------------------|----------------------|------------------------|-------|--|-------------------------|
| K- 07 10 12 95 | 6,3 | 7,9 | 75 | 15 | 13 | 2,5 |
| K- 07 10 12 96 | 6,3 | 7,9 | 75 | 30 | 13 | 5,0 |
| K- 07 10 12 97 | 6,3 | 7,9 | 75 | 45 | 13 | 7,5 |
| K- 07 10 12 65 | 7,9 | 9,5 | 115 | 10 | 12 | 2,5 |
| K- 07 10 12 66 | 7,9 | 9,5 | 115 | 20 | 12 | 5,0 |
| K- 07 10 12 67 | 7,9 | 9,5 | 115 | 30 | 12 | 7,5 |
| K- 07 10 12 68 | 9,5 | 11,8 | 140 | 8 | 11 | 2,5 |
| K- 07 10 12 69 | 9,5 | 11,8 | 140 | 15 | 11 | 5,0 |
| K- 07 10 12 70 | 9,5 | 11,8 | 140 | 23 | 11 | 7,5 |

Accessories

| | |
|---------------------------------|-------------------------------------|
| K-DREHBARE VERSCHR KNICK | Swivel adapters with kink protector |
| K-STARRE VERSCHRAUBUNG | Rigid adapters with kink protector |