

K-SPIR SCHL KUPPL SET STAND MS

Spiral hose and coupling kit with standard coupling and push-in plug, bare brass

HANSA FLEX

Properties

Pneumatic Type connection nipples and coupling NW 7,2

Operating temperature -40 °C to +74 °C



Note

Further information on request

Description

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Item					
Identification	Ø hose internal (mm)	Ø hose external (mm)	Ø external coil (mm)	Max. working pressure resistance at 23°C (bar)	max. working length (m)
K- 07 10 12 72	5,0	8,0	40	10	3,0
K- 07 10 12 74	5,0	8,0	40	10	6,0
K- 07 10 12 76	5,0	8,0	40	10	7,5
K- 07 10 12 81	6,3	9,5	60	10	3,0
K- 07 10 12 83	6,3	9,5	60	10	6,0
K- 07 10 12 85	6,3	9,5	60	10	7,5
K- 07 10 12 79	6,3	9,5	60	10	10,0
K- 07 10 12 90	8,0	12,0	80	9	3,0
K- 07 10 12 92	8,0	12,0	80	9	6,0
K- 07 10 12 94	8,0	12,0	80	9	7,5
K- 07 10 12 88	8,0	12,0	80	9	10,0

Accessories

K-DREHBARE VERSCHRAUBUNG Swivel adapters