

K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

HANSA FLEX

Properties

| | |
|------------------------------|--|
| Pneumatic Type | with pushbutton safety coupling NW 7,4 steel nipple galvanised |
| Operating temperature | -40 °C to +74 °C |



Note

Further information on request

Description

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Not suitable for striking or pulsating tools!

Item

| Identification | Ø hose internal (mm) | Ø hose external (mm) | Ø external coil (mm) | Max. working pressure resistance at 23°C (bar) | max. working length (m) |
|----------------|----------------------|----------------------|----------------------|--|-------------------------|
| K- 07 10 12 71 | 5,0 | 8,0 | 40 | 10 | 3,0 |
| K- 07 10 12 73 | 5,0 | 8,0 | 40 | 10 | 6,0 |
| K- 07 10 12 75 | 5,0 | 8,0 | 40 | 10 | 7,5 |
| K- 07 10 12 80 | 6,3 | 9,5 | 60 | 10 | 3,0 |
| K- 07 10 12 82 | 6,3 | 9,5 | 60 | 10 | 6,0 |
| K- 07 10 12 84 | 6,3 | 9,5 | 60 | 10 | 7,5 |
| K- 07 10 12 78 | 6,3 | 9,5 | 60 | 10 | 10,0 |
| K- 07 10 12 89 | 8,0 | 12,0 | 80 | 9 | 3,0 |
| K- 07 10 12 91 | 8,0 | 12,0 | 80 | 9 | 6,0 |
| K- 07 10 12 93 | 8,0 | 12,0 | 80 | 9 | 7,5 |
| K- 07 10 12 87 | 8,0 | 12,0 | 80 | 9 | 10,0 |

Accessories

K-DREHBARE VERSCHRAUBUNG Swivel adapters