


Properties			
Connection 1 + 2	BSP cylindrical internal threads		
Contact travel	0°; 90°		
Temp. range	Air: - 20 °C to + 150 °C Water: 0 °C to +150 °C		
Surface	nickel plated		
Material	Brass housing Aluminium handle Brass ball, hard chrome-plated PTFE ball seal		





Note

The pressure figures are applicable for temperatures from 0 °C to +25 °C; at higher temperatures, pressure reductions must be taken into account.

Ordering information

Other pressure and temperature figures available on request.

Item				
Identification	DN*	Connecting thread	Operating pressure	
BKR 06 ND	6	G 1/4" -19	50,0	
BKR 10 ND	10	G 3/8" -19	50,0	
BKR 13 ND	12	G 1/2" -14	50,0	
BKR 20 ND	19	G 3/4" -14	40,0	
BKR 25 ND	25	G 1" -11	40,0	
BKR 32 ND	31	G 1.1/4" -11	30,0	
BKR 40 ND	38	G 1.1/2" -11	30,0	
BKR 50 ND	51	G 2" -11	25,0	
BKR 65 ND	65	G 2.1/2" -11	18,0	
BKR 75 ND	76	G 3" -11	16,0	
BKR 100 ND	100	G 4" -11	14,0	

DN = Nominal diameter, nominal width

Spare parts		
ND GRIFF	Handle for ND ball valve	