

# BKR ND ROV

2-way ball valve in low pressure design

**HANSA FLEX**

## Properties

<b>Connection 1 + 2</b>	BSP cylindrical internal threads
<b>Sealing form 1 + 2</b>	for screw-in pins with shapes A, B and if necessary E
<b>Contact travel</b>	0°; 90°
<b>Temp. range</b>	Water: 0 °C to +130 °C Air: - 20 °C to +130 °C
<b>Surface</b>	nickel plated
<b>Material</b>	Brass housing Aluminium handle Brass ball, hard chrome-plated PTFE ball seal



## Note

The pressure figures are applicable for temperatures from 0 °C to +25 °C; at higher temperatures, pressure reductions must be taken into account.

## Description

With longer screw-in thread for pipe fittings to DIN 2353

## Ordering information

Other pressure and temperature figures available on request.

Item			
Identification	DN*	Connecting thread	Operating pressure (bar)
BKR 06 ND ROV	6	G 1/4" -19	64,0
BKR 10 ND ROV	10	G 3/8" -19	64,0
BKR 13 ND ROV	12	G 1/2" -14	50,0
BKR 20 ND ROV	19	G 3/4" -14	40,0
BKR 25 ND ROV	25	G 1" -11	40,0
BKR 32 ND ROV	31	G 1.1/4" -11	30,0
BKR 40 ND ROV	38	G 1.1/2" -11	30,0
BKR 50 ND ROV	51	G 2" -11	25,0

DN = Nominal diameter, nominal width

## Spare parts

**ND GRIFF** Handle for ND ball valve