



Properties	
Design	Wipers
Sliding speed max.	4,0 m/s
Temp. min.	-40 °C
Temp. max.	110 °C
Media	Mineral oil
Installation	bend the wiper into a kidney shape and press into the locating groove
Application	For the usage at higher pollution, for e.g.: Mining foundries
Material	PU 93° Shore A





Item							
Identification	С	D	d	Е	Н	L	
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
WAH-35	42,0	45,0	35	1,5	10,0	6,3	
WAH-36	41,5	44,0	36	1,5	8,0	5,0	
WAH-40	45,5	48,0	40	1,5	8,0	5,0	
WAH-45	50,5	53,0	45	1,5	8,0	5,0	
WAH-50	55,5	58,0	50	1,5	8,0	5,0	
WAH-56	63,0	66,0	56	1,5	10,0	6,3	
WAH-60	67,0	70,0	60	1,5	10,0	6,3	
WAH-63	70,0	73,0	63	1,5	10,0	6,3	_
WAH-70	78,4	82,6	70	2,0	12,0	8,0	
WAH-80	87,0	90,0	80	1,5	10,0	6,3	
WAH-90	96,0	102,2	90	2,8	12,4	7,1	