

K-FI FEIN HANSA PRO

Compressed air fine filter, with manual/semi-automatic condensate drain, HANSA PRO

HANSA FLEX

Properties

| | |
|--------------------------------|--|
| Media temperature | -10 °C to +50 °C |
| Ambient temperature | -10 °C to +50 °C |
| Media | Compressed air |
| Design | fiber filter |
| Mounting type | Line mounting, mounting kit or wall mounting |
| Installation position | Vertical, drain down |
| Filter rating | 0,01 µm |
| filter efficiency | 99.999 % |
| Nominal flow-rate G1/2 | 750 l/min (P1 = 6 bar/Delta P = 0,1 bar) |
| Nominal flow-rate G 3/8 | 750 l/min (P1 = 6 bar/Delta P = 0,1 bar) |
| Pe max | 16 bar |
| Filter element | Borsilicate-Al |
| Housing | PA66 |
| Residual oil content | 0,01 mg/m3 |



Item

| Identification | Connection | Container | Size | condensate outlet |
|----------------|------------|------------------------------------|------|-------------------------|
| K- 07 25 21 28 | G 3/8 i | polycarbonate with protective cage | 2 | manual / semi-automatic |
| K- 07 25 21 29 | G 1/2 i | polycarbonate with protective cage | 2 | manual / semi-automatic |
| K- 07 25 21 30 | G 3/8 i | zinc with visual display | 2 | manual / semi-automatic |
| K- 07 25 21 31 | G 1/2 i | zinc with visual display | 2 | manual / semi-automatic |