


# K-ROHRLEIT ALU KALIBRIERT BLAU INFI

Pipe made of aluminium, calibrated, blue

**HANSA FLEX**

## Properties

|                              |  |
|------------------------------|--|
| <b>Media</b>                 | Compressed air, vacuum, inert gases          |
| <b>expansion coefficient</b> | 0,024 mm/m °C                                |
| <b>Operating pressure</b>    | -0,99 bar - 15 bar                           |
| <b>Temp. range</b>           | -20 °C to +80 °C                             |
| <b>Colour</b>                | blue RAL 5010                                |
| <b>Material</b>              | Aluminium UNI 9006/1 Al Mg 0,5 Si 0,4 Fe 0,2 |
| <b>Surface treatment</b>     | electrostatic coating                        |



## Ordering information

Special lengths on request

| Item           |                    |                        |                      |                                  |               |                |
|----------------|--------------------|------------------------|----------------------|----------------------------------|---------------|----------------|
| Identification | External Ø<br>(mm) | Wall thickness<br>(mm) | Weight per m<br>(kg) | density specific per dm3<br>(kg) | Length<br>(m) | Packaging unit |
| K- 07 40 53 09 | 20                 | 1,5                    | 0,235                | 2,7                              | 4,000         | 1 piece        |
| K- 07 40 53 23 | 20                 | 1,5                    | 0,235                | 2,7                              | 6,000         | 1 piece        |
| K- 07 40 53 10 | 25                 | 1,5                    | 0,298                | 2,7                              | 4,000         | 1 piece        |
| K- 07 40 53 24 | 25                 | 1,5                    | 0,298                | 2,7                              | 6,000         | 1 piece        |
| K- 07 40 53 11 | 32                 | 1,5                    | 0,387                | 2,7                              | 4,000         | 1 piece        |
| K- 07 40 53 25 | 32                 | 1,5                    | 0,387                | 2,7                              | 6,000         | 1 piece        |
| K- 07 40 53 12 | 40                 | 1,5                    | 0,490                | 2,7                              | 4,000         | 1 piece        |
| K- 07 40 53 26 | 40                 | 1,5                    | 0,490                | 2,7                              | 6,000         | 1 piece        |
| K- 07 40 53 13 | 50                 | 2,0                    | 0,814                | 2,7                              | 4,000         | 1 piece        |
| K- 07 40 53 27 | 50                 | 2,0                    | 0,814                | 2,7                              | 6,000         | 1 piece        |
| K- 07 40 53 14 | 63                 | 2,0                    | 1,034                | 2,7                              | 4,000         | 1 piece        |
| K- 07 40 53 28 | 63                 | 2,0                    | 1,034                | 2,7                              | 6,000         | 1 piece        |
| K- 07 40 55 07 | 80                 | 2,0                    | 1,493                | 2,7                              | 4,000         | 1 piece        |
| K- 07 40 55 09 | 80                 | 2,0                    | 1,493                | 2,7                              | 6,000         | 1 piece        |
| K- 07 40 53 22 | 110                | 2,5                    | 2,280                | 2,7                              | 4,000         | 1 piece        |
| K- 07 40 53 29 | 110                | 2,5                    | 2,280                | 2,7                              | 6,000         | 1 piece        |