

K-ROHRLEIT ALU KALIBRIERT BLAU INFI

Pipe made of aluminium, calibrated, blue

HANSA FLEX

Properties

| | |
|-----------------------|--|
| Media | Compressed air, vacuum, inert gases |
| expansion coefficient | 0,024 mm/m °C |
| Operating pressure | -0,99 bar - 15 bar |
| Temp. range | -20 °C to +80 °C |
| Colour | blue RAL 5010 |
| Material | Aluminium UNI 9006/1 Al Mg 0,5 Si 0,4 Fe 0,2 |
| Surface treatment | electrostatic coating |



Ordering information

Special lengths on request

| Item | | | | | | |
|----------------|--------------------|------------------------|----------------------|----------------------------------|---------------|----------------|
| Identification | External Ø (mm) | Wall thickness (mm) | Weight per m (kg) | density specific per dm3 (kg) | Length (m) | Packaging unit |
| K- 07 40 53 09 | 20 | 1,5 | 0,235 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 23 | 20 | 1,5 | 0,235 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 10 | 25 | 1,5 | 0,298 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 24 | 25 | 1,5 | 0,298 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 11 | 32 | 1,5 | 0,387 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 25 | 32 | 1,5 | 0,387 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 12 | 40 | 1,5 | 0,490 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 26 | 40 | 1,5 | 0,490 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 13 | 50 | 2,0 | 0,814 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 27 | 50 | 2,0 | 0,814 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 14 | 63 | 2,0 | 1,034 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 28 | 63 | 2,0 | 1,034 | 2,7 | 6,000 | 1 piece |
| K- 07 40 55 07 | 80 | 2,0 | 1,493 | 2,7 | 4,000 | 1 piece |
| K- 07 40 55 09 | 80 | 2,0 | 1,493 | 2,7 | 6,000 | 1 piece |
| K- 07 40 53 22 | 110 | 2,5 | 2,280 | 2,7 | 4,000 | 1 piece |
| K- 07 40 53 29 | 110 | 2,5 | 2,280 | 2,7 | 6,000 | 1 piece |