
## K-STECK VS 20-50 INFI

press-lock Ø 20 mm – Ø 63 mm



| Properties         |                                     |
|--------------------|-------------------------------------|
| Media              | Compressed air, vacuum, inert gases |
| Operating pressure | -0,99 bar - 15 bar                  |
| Temp. range        | -20 °C to +80 °C                    |
| Seal               | NBR                                 |
| Housing            | Nickel-plated brass                 |
| Clamp ring         | Stainless steel 1.4301              |
| Nut                | Nickel-plated brass                 |
| O-ring             | NBR                                 |
| Locking ring       | Technopolymer                       |





| Identification | External pipe Ø | E    | L    | AF2  |
|----------------|-----------------|------|------|------|
|                |                 | (mm) | (mm) | (mm) |
| K- 07 40 54 20 | 20 mm           | 34,5 | 33,0 | 30   |
| K- 07 40 54 21 | 25 mm           | 42,5 | 39,0 | 35   |
| K- 07 40 54 22 | 32 mm           | 52,0 | 46,5 | 45   |
| K- 07 40 54 23 | 40 mm           | 63,0 | 53,0 | 55   |
| K- 07 40 54 24 | 50 mm           | 73,0 | 62,0 | 65   |
| K- 07 40 55 04 | 63 mm           | 94,0 | 54,0 | 75   |