

# K-W STECK VB 2-FACH WAND 20-63 INFI

2-fold angle connector Ø 20 mm - Ø 63 mm with wall mounting (adjustable)

**HANSA FLEX**

## Properties

<b>Media</b>	Compressed air, vacuum, inert gases
<b>Operating pressure</b>	-0,99 bar - 15 bar
<b>Temp. range</b>	-20 °C to +80 °C
<b>Seal</b>	NBR
<b>Housing</b>	Nickel-plated brass
<b>Clamp ring</b>	Stainless steel 1.4301
<b>Nut</b>	Nickel-plated brass
<b>O-ring</b>	NBR
<b>Locking ring</b>	Technopolymer



## Item

Identification	External pipe Ø	Connection	B	C	E	I	L1	L2	L max	L min	M	N	O	P	AF1	AF2
			(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
K- 07 40 54 14	20 mm	G 1/2"	31,5	20,0	34,5	28,5	27,0	51,5	54	22	74	61	30,5	5	26	30
K- 07 40 54 15	25 mm	G 1/2"	38,5	21,0	42,5	28,5	27,0	59,0	54	22	74	61	30,5	5	26	35