
# K-DRUCKVERST MANO SCHALLD VBA

Booster Regulator, pressure gauge, silencer, VBA

## Properties

| | |
|---|---|
| **Design** | with pressure gauge and silencer |
| **min. working pressure** | 0.20 MPa |
| **Port for pneumatic pressure gauge** | Rc 1/8 |
| **number connection pneumatic pressure gauge** | 2 |
| **max. inlet pressure** | 0,1 to 1,0 MPa |
| **Media temperature** | +2 °C to +50 °C |
| **Ambient temperature** | +2 °C bis +50 °C |
| **Media** | Compressed air |



## Description

Booster regulator, series VBA, increases pressure only where the force is inadequate because of a low network pressure (energy saving measure), no electricity supply necessary, longer service life: doubled compared to conventional model, lower operating noise level: 13 dB (A), improved operational reliability from inbuilt mesh filter on (IN connection) compressed air inlet, reduced condensation levels: air exhaust channels integrated directly into the cylinder tube, suitable for: compressed air, size 1/4, with pressure gauge and silencer, elbow, pneumatic connection: G 1/4, pneumatic connection pressure gauge: G 1/8, pneumatic connections pressure gauge: 2, flow rate 230 l/min, pressure boost 1:2, manually actuated pressure adjustment mechanism, test pressure: 3 MPa, max. operating pressure: 2 MPa, min. operating pressure: 0.2 MPa, media temperature: +2 to +50 °C, ambient temperature: +2 to +50 °C

## Item

| Identification | Pneumatic Port | Size | pressure adjustment mechanism | pressure booster ratio | Flow rate (L/min) | Max. working pressure (MPa) | Test pressure (MPa) |
|---|---|---|---|---|---|---|---|
| **K- 07 60 00 07** | G 1/4 | 1/4 | manually operated | 1:2 to 1:4 | 70 | 2,00 | 3,00 |
| **K- 07 60 00 05** | G 1/4 | 1/4 | manually operated | 1:2 | 230 | 2,00 | 3,00 |
| **K- 07 60 00 10** | G 3/8 | 3/8 | manually operated | 1:2 | 1000 | 1,00 | 1,50 |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*