

# K-DRUCKVERST MANO SCHALLD W VBA

Booster Regulator, pressure gauge, elbow silencer, VBA

**HANSA FLEX**

## Properties

<b>Design</b>	with pressure gauge and silencer, angled
<b>min. working pressure</b>	0.20 MPa
<b>Port for pneumatic pressure gauge</b>	Rc 1/8
<b>number connection pneumatic pressure gauge</b>	2
<b>max. inlet pressure</b>	0,1 to 1,0 MPa
<b>Media temperature</b>	+2 °C to +50 °C
<b>Ambient temperature</b>	+2 °C bis +50 °C
<b>Media</b>	Compressed air



## Description

Booster regulator, series VBA, increases pressure only where the force is inadequate because of a low network pressure (energy saving measure), no electricity supply necessary, longer service life: doubled compared to conventional model, lower operating noise level: 13 dB (A), improved operational reliability from inbuilt mesh filter on (IN connection) compressed air inlet, reduced condensation levels: air exhaust channels integrated directly into the cylinder tube, suitable for: compressed air, size 1/4, with pressure gauge and silencer, elbow, pneumatic connection: G 1/4, pneumatic connection pressure gauge: G 1/8, pneumatic connections pressure gauge: 2, flow rate 230 l/min, pressure boost 1:2, manually actuated pressure adjustment mechanism, test pressure: 3 MPa, max. operating pressure: 2 MPa, min. operating pressure: 0.2 MPa, media temperature: +2 to +50 °C, ambient temperature: +2 to +50 °C

## Item

Identification	Pneumatic Port	Size	pressure adjustment mechanism	pressure booster ratio	Flow rate	Max. working pressure	Test pressure
					(L/min)	(MPa)	(MPa)
K- 07 60 00 03	G 1/4	1/4	manually operated	1:2	230	2,00	3,00