

K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

HANSA FLEX

Properties

| | |
|------------------------------|--|
| Max. working pressure | 0,7 MPa |
| min. working pressure | 0.10 MPa |
| Design | rack and pinion |
| Media temperature | 0 °C to +60 °C |
| Ambient temperature | 0 °C to +60 °C |
| Swivel angle | 0 to 190° |
| Media | Compressed air |
| Series | MSQ |
| More information | narrow pivot table unit with low overall height the rotation angle can be adjusted continuously Positioning the housing allow for quick installation the load can be mounted directly on the pivot table Air connections of 2 pages possible |



Item

| Identification | Ø piston (mm) | Pneumatic Port | Size | Damping | Weight per m (kg) |
|----------------|---------------|----------------|------|---|-------------------|
| K- 07 55 01 13 | 6 | M 3 | 1 | without, with adjustment bolt | 0,075 |
| K- 07 55 01 18 | 8 | M 5 | 2 | without, with adjustment bolt | 0,105 |
| K- 07 55 01 21 | 10 | M 5 | 3 | elastic, with adjustment bolt | 0,150 |
| K- 07 55 01 26 | 12 | M 5 | 7 | elastic, with adjustment bolt | 0,250 |
| K- 07 55 01 11 | 15 | M 5 | 10 | elastic, with adjustment bolt | 0,530 |
| K- 07 55 01 16 | 18 | M 5 | 20 | elastic, with adjustment bolt | 0,990 |
| K- 07 55 01 19 | 21 | G 1/8 | 30 | elastic, with adjustment bolt | 1,290 |
| K- 07 55 01 22 | 25 | G 1/8 | 50 | elastic, with adjustment bolt | 2,080 |
| K- 07 55 01 24 | 28 | G 1/8 | 70 | elastic, with adjustment bolt | 2,880 |
| K- 07 55 01 09 | 32 | G 1/8 | 100 | elastic, with adjustment bolt | 4,090 |
| K- 07 55 01 14 | 40 | G 1/8 | 200 | elastic, with adjustment bolt | 7,580 |
| K- 07 55 01 12 | 15 | M 5 | 10 | elastic, with integrated shock absorber | 0,540 |
| K- 07 55 01 17 | 18 | M 5 | 20 | elastic, with integrated shock absorber | 0,990 |
| K- 07 55 01 20 | 21 | G 1/8 | 30 | elastic, with integrated shock absorber | 1,290 |
| K- 07 55 01 23 | 25 | G 1/8 | 50 | elastic, with integrated shock absorber | 2,100 |
| K- 07 55 01 25 | 28 | G 1/8 | 70 | elastic, with integrated shock absorber | 2,880 |
| K- 07 55 01 10 | 32 | G 1/8 | 100 | elastic, with integrated shock absorber | 4,100 |
| K- 07 55 01 15 | 40 | G 1/8 | 200 | elastic, with integrated shock absorber | 7,650 |