SKM HM ED AGRAR

Plug-in coupling sleeve



Properties				
Application	Agricultural technology Industry			
Connection 1	metric cylindrical outer thread			
Sealing form 1	Shape E			
Standard	complies with ISO 7241 series A			
Operating pressure	max. 250 bar			
Volumetric flow	max. 240 l/min, in combination with SKS Agrar			
Additional feature	Limited pressure loss High-flow valve uni Mechanical locking system Push-pull function interchangeable with Parker RSD 501 can be coupled under pressure			
Temp. range	-30 °C to +100 °C			
Material	Steel			
Surface	electro galvanised			



Note

With standard threaded connections in determining the operating pressure of the maximum rated pressure is taken into account.

Description

The newly developed single-hand coupling sleeve can be engaged in the coupling connector under full operating pressure. Further advantages include the breakaway function and the lower coupling and uncoupling force.

Additional information

The coupling Agrar exceeds the requirements of ISO 7241-1 series A and ISO 5675 for the agricultural sector and is uncompromisingly designed for maximum efficiency. The Agrar male connector and Agrar sleeve system achieves a maximum volumetric flow of 240 litres per minute - a record level. Operation in heavy-duty tractors and implements such as tippers, is now safe.

The coupling sleeve is available in two different overall lengths and is therefore compatible with the common commercially available built-in couplings.

Item

Identification	DN*	Connecting thread	AF (mm)	Size	L1 (mm)	L2 (mm)	SF coup.*	Weight (kg)
SKM 13 HM 3 ED AGRAR	12	M 22x1,5	38	3	97,5	14,0	4	0,475

DN = Nominal diameter, nominal width - SF gek. = Safety factor coupled