SKM IR L AGRAR

Plug-in coupling sleeve



Properties

Properties					
Application	Agricultural technology Industry				
Connection 1	BSP cylindrical internal threads				
Sealing form 1	for screw-in pins with shapes A, B and if necessary E				
Standard	complies with ISO 7241 series A				
Operating pressure	max. 250 bar				
Volumetric flow	max. 240 l/min, in combination with SKS Agrar				
Additional feature	Limited pressure loss High-flow valve uni Mechanical locking system Push-pull function can be coupled under pressure interchangeable with Faster 3CFPV				
Temp. range	-30 °C to +100 °C				
Material	Steel				
Surface	electro galvanised				



Note

With standard threaded connections in determining the operating pressure of the maximum rated pressure is taken into account.

Description

The newly developed single-hand coupling sleeve can be engaged in the coupling connector under full operating pressure. Further advantages include the breakaway function and the lower coupling and uncoupling force.

Additional information

The coupling Agrar exceeds the requirements of ISO 7241-1 series A and ISO 5675 for the agricultural sector and is uncompromisingly designed for maximum efficiency. The Agrar male connector and Agrar sleeve system achieves a maximum volumetric flow of 240 litres per minute - a record level. Operation in heavy-duty tractors and implements such as tippers, is now safe.

The coupling sleeve is available in two different overall lengths and is therefore compatible with the common commercially available built-in couplings.

Identification	DN*	Connecting thread	AF (mm)	Size	L1 (mm)	L2 (mm)	Туре	SF coup.*	Weight (kg)
SKM 13 IR 3 L AGRAR	12	G 1/2" -14	32	3	107,3	15,0	Long	4	0,608

Accessories

SKM ZUBS 3 C	Dust protection coupling sleeve, SKM
SKM ZUBS 3 CB	Dust protection coupling sleeve, SKM