


Properties

Scope of supply	1 measuring device HK MH 2025
	1 USB-power supply unit 5 VDC, 500 mA
	2 NiMH rechargeable batteries
	2 pressure sensors with moulded cable (length 2.5 m), pressure ranges, see table
	2 MINIMESS® direct connectors for pressure sensors
	Software
	Operating manual
	Plastic case
Temp. range	-20 °C to +70 °C



Description

Compact measuring device
Direct handling by 5 softkeys
2 channels for industrial sensors (optional 0-20 mA, 4-20 mA, 0-10 V, 2-10 V, frequency, counter)
Calculation of differential pressure or power from 2 channels
ISDS automatic sensor detection
LCD graphic display with switched-mode backlight and automatic display adjustment
2,0 MB memory (5 series of measurements with 120,000 measured values)
Scanning rate selectable in 5 stages between 1 ms and 10 s
Display rate selectable between 0,5 ms and 10 ms
High-speed data transmission to the PC via USB interface
With software HYDROlink Base
Lightweight plastic housing with battery compartment for commercially available NiMH rechargeable batteries
Case dimensions: W=235 mm / L=185 mm / H=48 mm

Item

Identification	Pressure sensors included	Weight (kg)
HK MH2025 400 400	2x 0 - 400 bar	3,5
HK MH2025 060 600	1x 0 - 60 bar/1x 0 - 600 bar	3,5

Accessories

HK PT2020	Pressure sensor
-----------	-----------------