


Properties				
Design	Safety valve			
Operating pressure	max. 350 bar			
Additional feature	with TÜV certification			
Material	Gasket: NBR			
Connection	for accumulator M33x2			





## Note

Safety valve is preset; observe the maximum pressure when allocating to the corresponding accumulator!

## **Description**

The safety and isolation block is used to protect, shut off and discharge hydraulic accumulators. It is designed and manufactured in accordance with Directive 2014/68/EU (PED), Article 3 Para. 3 and takes into account the European safety regulations for the operation of hydraulic accumulators. Discharging the accumulator is done manually at a ball valve or a relief valve.

Viscosity of the fluids must lie within the following limits:

min. 10 mm2/s, max. 380 mm2/s

Item														
Identification	p max. (bar)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	F1 (mm)	G (mm)	M1	M2	Р	Т	Weight (kg)
HK SAB 10 M 100 N	100	120	98	29	50	24	73	75	101	1/4"	1/4"	1/2"	1/2"	4,2
HK SAB 10 M 200 N	200	120	98	29	50	24	73	75	101	1/4"	1/4"	1/2"	1/2"	4,2
HK SAB 10 M 210 N	210	120	98	29	50	24	73	75	101	1/4"	1/4"	1/2"	1/2"	4,2
HK SAB 10 M 250 N	250	120	98	29	50	24	73	75	101	1/4"	1/4"	1/2"	1/2"	4,2
HK SAB 10 M 330 N	330	120	98	29	50	24	73	75	101	1/4"	1/4"	1/2"	1/2"	4,2
HK SAB 20 M 330 N	330	98	120	39	71	25	73	90	184	1/2"	1/4"	1"	3/4"	6,6

## **Accessories**

HK AS Accumulator adapters for safety and isolation block
HK MSM Lock nuts for diaphragm accumulator C

Accessory for following products				
HK OLM A	Diaphragm accumulator, connection A			
HK OLM C	Diaphragm accumulator, connection C			
HK BLAK	Bladder accumulator			