


## Properties

<b>Design</b>	for DIN-rail 35x7,5 4 fast plug-in connectors RJ45 connector for RS232 serial communication with PC software 4 LEDs for diagnostics Electrical protection against reverse polarity
<b>Operating temperature max.</b>	60 °C
<b>Use</b>	for single solenoid and double solenoid proportional valves without transducer



## Description

for single solenoid and double solenoid proportional valves without transducer  
 Power supply standard: +24 VDC rectified and filtered  
 Max. power consumption: 50 W / 100 W  
 Max. current supplied to solenoids: 2,7 A at 24 VDC / 3,3 A at 12 VDC  
 Reference input signal:  $\pm 10$  VDC /  $\pm 20$  mA  
 Mounting for DIN-rail 35x7,5

## Item

Identification	for valve type	Weight (kg)
HK E BM AS PS 01H	Single solenoid for proportional valves	0,2
HK E BM AS PS 05H	Double solenoid for proportional valves	0,2

## Accessory for following products

HK DHZO A	Proportional solenoid-operated directional control valve size 6
HK DKZOR A	Proportional solenoid-operated directional control valve size 10
HK HZGO A 031	Proportional pressure reducing valve size 6
HK HZMO A 030	Proportional pressure relief valve size 6
HK KZGO A 031	Proportional pressure reducing valve size 10
HK RZGO A 033	Proportional pressure reducing valve size 6
HK RZMO A 010	Proportional pressure relief valve size 6
HK RZMO A 030	Proportional pressure relief valve size 6

## Additional elements

HK EA EC	Adapter cables
----------	----------------